

PHOENIX TITAN TWIN SPECIFICATIONS

ENGINE:

- Kawasaki FH541V 17 hp Air Cooled V-Twin
- UL Listed, EPA & CARB Approved
- Operating Noise Level 88 db
- Oil Filter
- Catalytic Muffler Including Spark Arrester
- Carbon Monoxide Exhaust Emissions .01 percent = 100 ppm Under Load
- 12V Battery Start
- Full Warning System Includes Lights and Low Oil Pressure/Auto Shut Off

GEARING:

- | | |
|-----------------------|----------------------|
| FRONT: | REAR: |
| - Belt Drive | - Belt Drive |
| - Dual Cogged V Belts | - Cogged V Belt |
| - 1000 rpm Pad Speed | - 1800 rpm Pad Speed |

PAD PRESSURE:

- | | |
|--------|-------|
| FRONT: | REAR: |
| - 55# | - 8# |

MACHINE MAIN FRAME:

- 7 Gauge Steel
- Surface Finish Powder Coat
- Built in Spray Pump
- Center Feed Spray
- 1 Gallon Spray Capacity

UPPER HANDLE:

- Adjustable
- Built in Hour Meter
- Kill Switch
- Throttle Control

24" PAD HOLDER:

- | | |
|-----------------------------|-----------------------------|
| FRONT: | REAR: |
| - Foam Insert | - Flex Disc Daisy Design |
| - Quick Release Center Lock | - Quick Release Center Lock |

MISCELLANEOUS:

- Weight 300#
- Height 43"
- Length 63"

OPTIONS:

- Emission monitor which will first warn by way of light and horn, then shutdown when emissions exceed a specified point.
- Automatic Spray Device
- Automatic Pad Change Reminder